

## Method for calibration of a wideband lambda probe used in internal combustion engines

**Patent number:** EP1079090

**Publication date:** 2001-02-28

**Inventor:** BIZENBERGER THOMAS (DE); DAETZ MICHAEL DIPL-ING (DE); JELDEN HANNO DIPL-ING (DE); KIELMANN CHRISTOPH (DE)

**Applicant:** VOLKSWAGENWERK AG (DE)

**Classification:**

- **international:** F02D41/14; G01N27/417

- **european:** F02D41/14D3H4; F02D41/24D4B

**Application number:** EP20000116857 20000804

**Priority number(s):** DE19991039555 19990820

**Also published as:**

EP1079090 (A3)  
DE19939555 (A)

**Cited documents:**

US5845624  
US4751907  
US4909223  
US5323635

[Report a data error](#) [he](#)

### Abstract of EP1079090

To calibrate the sensor and compensate for manufacturing tolerances a correction value is determined as follows. With the engine running with  $\lambda = 1$  a fuel mass  $m_{K1}$  and air mass flow  $m_{L1}$  are determined. Then with  $\lambda = 1$  (lean or fat mixture) values  $m_{K2}$  and  $m_{L2}$  are measured. Based on these values the correction value for the condition  $\lambda = 1$  is derived

Data supplied from the **esp@cenet** database - Worldwide